





































































	1-oct-18			
NVR Recorders				TRADE PL
Model	Product image	Camera inputs	Description	Vatu (Ex-Vat)
NVR Recorders				
301 Series NVR(1 HDD)				
NVR301-04LB-P4-1TB		4-Ch	UNV NVR 4CH 1SATA 4PoE 1TB ECO 2MP max res. 4-ch, 1 SATA HDD, 1-HDMI/1-VGA output, 1x USB 2.0, 1x USB 3.0, Mini 1RU, 1 x GigE, 4x PoE ports	VT 30,600
NVR301-04P4-2TB		4-Ch	4-ch, 1 SATA HDD, 1-HDMI/1-VGA output, 1x USB 2.0, 1x USB 3.0, Mini 1RU, 1 x GigE, 4x PoE ports	VT 37,800
NVR301-08P8-3TB		8-Ch	4-ch, 1 SATA HDD, 1-HDMI/1-VGA output, 1x USB 2.0, 1x USB 3.0, Mini 1RU, 1 x GigE, 8x PoE ports	VT 44,400
NVR301-08S		8-ch	8ch 12VNVR, 1 SATA HDD, 1-HDMI/1-VGA output, 1x USB 2.0, 1x USB 3.0, Mini 1RU	VT 18,600
KIT A		4ch + 2cam	UNV KIT NVR 4CH + 2TB HDD with 2x 5MP turret	VT 59,760
KIT B		4ch + 4cam	UNV KIT NVR 4CH + 2TB HDD with 4x 5MP turret	VT 92,400
KIT C		8ch + 4cam	UNV KIT NVR 8CH + 3TB HDD with 4x 5MP turret	VT 107,400
NVR201-04U-1TB HYBRID RECORDER		4ch +2IP Hybrid	Support AHD input: 5MP, 4MP, 3MP, 1080P/30Hz, 1080P/25Hz, 720P/30 Hz, 720P/25 Hz, Support TVI input: 5MP, 3MP, 1080P/30Hz, 1080P/25Hz, 720P/30 Hz, 720P/25 Hz Support CVI input: 1080P/25Hz, 1080P/30Hz, 720P/25Hz, 720P/30Hz Support CVBS input	VT 29,400
NVR201-08Q-2TB HYBRID RECORDER		8ch +2IP Hybrid	Support AHD input: 3MP, 1080P/30 Hz, 1080P/25 Hz, 720P/25 Hz, 720P/30 Hz Support TVI input: 3MP, 1080P/30 Hz, 1080P/25 Hz, 720P/25 Hz, 720P/30 Hz Support CVI input: 1080P/25Hz, 1080P/30Hz, 720P/25Hz, 720P/30Hz Support CVBS input	VT 32,400
302 Series NVR(2 HDDs)				
NVR302-08EP-3TB		8-Ch	8-ch, 2 SATA HDDs, 1-HDMI/1-VGA output, 1x USB 2.0, 1x USB 3.0, Mini 1RU, 1 x GigE, 8x PoE ports.	VT 70,800
NVR302-16EP-B-4TB		16-Ch	16-ch, 2 SATA HDDs, 1-HDMI/1-VGA output, 1x USB 2.0, 1x USB 3.0, Mini 1RU, 1 x GigE, 16x PoE ports.	VT 90,960
NVR302-16SP-3TB		16-Ch	16-ch, 2 SATA HDDs, 1-HDMI/1-VGA output, 1x USB 2.0, 1x USB 3.0, Mini 1RU, 1 x GigE, 16x PoE ports.	VT 63,000

















Model	Product image	Camera inputs	Description	Vatu (Ex-Vat)
304 Series NVR(4 HDDs)				
NVR304-32EP-4TB		32-Ch	32-ch, 4 SATA HDDs (Up to 6TB each), H264/H265, 1xVGA, 2xHDMI (HDMI 2 supports 4k), USB 2.0, 1 USB 3.0, -10°C to 55°C, 2RU, 1 x GigE Now includes 4TB installed	VT 107,880
308 Series NVR(8 HDDs)				
NVR308-64E 4TB		64-Ch	64-ch, 8 SATA interface, 2U, H.265&4K, Dual Network interface, RAID1, RAID5, Hard disk hot swap on front panel,	VT 126,000
516 Series NVR(16 HDDs)				
NVR516-128		128-Ch	128-ch, 16 SATA interface, 3U, H.265&4K, 4 Network interface, 2 SFP interface, RAID1, RAID5, Hard disk hot swap on front panel, Redundant power supply (optional), Up to 14 HDMI output (optional), 2 miniSAS ports.	VT 424,200
FB-HDMI4-C-NB			4x HDMI outputs 64x720P 32 x 1080P 16 x 4MP 8 x 4K	VT 134,400
FB-HDMI6-C-NB			6x HDMI Outputs 96 x 720P 48 x 1080P 24 x 4MP 12 x 4K	VT 190,800
PWR-300A-IN			UNV Redundant Power Supply for NVR516	VT 46,800
DEU1008			TBC	VT 146,400
DEU1016			TBC	VT 270,000
Decoders				
KIT-DC5301-PWR1			1-ch H.265&4K Decoder, with power adapter	VT 123,600
DC4304-IN			H.264 video compression, ONVIF conformance stream decoding Video decoding up to 1080P, DVI-I output up to 1080P, compatible with HDMI/DVI-D/ and VGA Video input 1/4/9/16 display split	VT 220,800
DC4308-IN			H.264 video compression, ONVIF conformance stream decoding Video decoding up to 1080P, DVI-I output up to 1080P, compatible with HDMI/DVI-D/VGA HDMI and VGA Video input 1/4/9/16 display split	VT 282,000











Model	Product image	Camera inputs	Description	Vatu (Ex-Vat)
Switches				
NSW2000-8T1GC-POE			NSW2000-8T1GC-POE is an 8-port PoE switch, which provides 8 10/100Mbps PoE ports and 1 Gigabit combo port. All ports support wire speed, non-blocking switching and auto MDI/MDIX. Besides common switch features, supports EXTEND mode special for video surveillance. When EXTEND mode is enabled, the transmission distance with Uniview IPC can reach up to 250m.	VT 28,200
NSW2000-16T2GC-POE			NSW2000-16T2GC-POE is an 16-port PoE switch, which provides 16 10/100Mbps PoE ports and 2 Gigabit combo ports. All ports support wire speed, non-blocking switching and auto MDI/MDIX. Besides common switch features, NSW2000-16T2GC-POE supports EXTEND mode special for video surveillance. When EXTEND mode is enabled, the transmission distance with Uniview IPC can reach up to 250m.	VT 46,200
NSW2000-24T2GC-POE			NSW2000-24T2GC-POE is an 24-port PoE switch, which provides 24 10/100Mbps PoE ports and 2 Gigabit combo ports. All ports support wire speed, non-blocking switching and auto MDI/MDIX. Besides common switch features, NSW2000-24T2GC-POE supports EXTEND mode special for video surveillance. When EXTEND mode is enabled, the transmission distance with Uniview IPC can reach up to 250m.	VT 55,800
Keyboard				
KB-1100			Network Keyboard	VT 58,200
Monitor				
MW3222-F			UNV Monitor 22 inch 1920×1080 "170°(H) 160°(V)", 250cd/m², 1000:1, 1.5W x 2, DVI/VGA/HDMI	VT 22,800
MW3232-E			UNV Monitor 32" VGA HDMI DVI Wide view of field:178°(H)/178°(V) full HD 1920×1080, Brightness 280 cd/m2, Contrast 1200:1, Vesa Mount, DVI/VGA/HDMI	VT 99,000
MW3243-E			UNV Monitor 43" VGA HDMI DVI Wide view of field:178°(H)/178°(V) full HD 1920×1080, Brightness 300 cd/m2, Contrast 1200:1, Vesa Mount, DVI/VGA/HDMI	VT 160,200

Model	Product image	Camera inputs	Description	Vatu (Ex-Vat)
Dome Cameras				
IPC3615-ADUPF28M		5MP	1/2.7", progressive scan, 5.0 megapixel, CMOS, Lens 2.8mm@F1.6 Angle of view(H) 105.75° 86.9° Minimum Illumination Colour: 0.005Lux (F1.6, AGC ON) 0 Lux with IR-cut filter with auto switch (ICR), IR Range Up to 30m IR range, Digital Defog, WDR -120dB, HLC, BLC, Corridor Mode, Smarts	VT 18,000
IPC3615LR3-PF28D		5MP	1/2.7", 5.0 megapixel, progressive scan, CMOS, 2.8mm@F2.0, IR Up to 30m, DWDR, Main Stream: 5MP (2592*1944): Max. 15 fps, Sub Stream: 720P (1280*720): Max. 20 fps,	VT 15,600
IPC3614LR3-PF28D		4MP	1/3", 4.0 megapixel, progressive scan, CMOS, 2.8mm@F2.0, IR Up to 30m, DWDR, Main Stream: 4MP (2592*1520): Max. 20 fps, Sub Stream: 720P (1280*720): Max. 30 fps, Third Stream: D1 (720*576): Max. 30 fps,	VT 13,200
IPC325LR3VSPF28D		5MP	1/2.7", progressive scan, 5.0 megapixel, CMOS, 2.8mm@F2.0, IR Up to 30m, DWDR, Main Stream: 5MP (2592*1944): Max. 15 fps, Sub Stream: 720P (1280*720): Max. 20 fps, IP67, IK10	VT 16,200
IPC322-DUVPF28		2MP	1/2.9" CMOS, ICR, 1920x1080:25fps, H.264/MJPEG, Dual streams, DC12V & PoE(200m@10Mbps&Cat6), 120dB WDR, 3D DNR, ROI, Alarm in/out 1/1, Audio, -35~60°C, IP66 & IK10, Fixed 2.8mm or 3.6mm lens), IR range: up to 30m New 3 axis version	VT 21,600
IPC314SR-VPF28		4MP	1/2.8" CMOS, ICR, 1920x1080:25fps, H.264/H265, Dual streams, DC12V & PoE(200m@10Mbps&Cat6), 3D DNR, ROI, Alarm in/out 1/1, Audio, -35~60°C, IP66 & IK10, Fixed 2.8mm lens, (3.6mm optional lens), IR range: up to 30m	VT 18,600
IPC3635ER3-DUPZ		5MP	1/2.7", progressive scan, 5.0 megapixel, CMOS, Lens 2.7~13.5mm, AF automatic focusing and motorized zoom lens, Minimum Illumination Colour: 0.001 Lux (F1.2, AGC ON) 0 Lux with IR, IR Range Up to 30m IR range, Digital Defog, WDR -120dB, Digital noise reduction 2D/3D DNR S/N >52dB	VT 27,600
IPC3638SR3-DPZ		4K	1/2", progressive scan, 8.0 megapixel, CMOS, 2.8~12mm, AF automatic focusing and motorized zoom lens, Colour: 0.003 Lux (F1.5, AGC ON) 0 Lux with IR, IR-cut filter with auto switch (ICR), Up to 30m (98 ft) IR range, WDR 120dB, Behavior Detection, Intrusion, cross line, motion detection, Face detection, Audio detection, People counting.	VT 45,000
IPC3235ER3-DUVZ		5MP	1/2.7", progressive scan, 5.0 megapixel, CMOS, 2.7~13.5mm, AF automatic focusing and motorized zoom lens, Angle of View (H) 93.38°~28.56°(H), Colour: 0.001 Lux (F1.2, AGC ON), Digital noise reduction IR Range up to 30m (98 ft) IR range Digital Defog WDR 120dB	VT 29,400
IPC3232ER3-DUVZ		2MP	1/2.8" CMOS, ICR, 1920x1080:30fps, H.265/H.264/MJPEG, Triple stream, DC12V & PoE, 120dB WDR, Micro SD card slot, Alarm in/out 2/1, Audio, BNC output, IP66 & IK10, 2.8-12mm, 4X optical zoom, IR range: up to 30m. Ultra low-light (Starlight)	VT 82,800
IPC3238ER3-DVZ NEW		4K	1/2.5", 8 megapixel, progressive scan CMOS, 2.8~12mm@F1.6, Smart-IR, up to 30m (98 ft) IR range, True WDR 120dB, Max. Resolution 3840x2160, H.265, H.264, MJPEG, 4K (3840x2160): Max. 30 fps; 1080P (1920x1080): Max. 30fps	VT 54,000
IPC814SR-DVPF16		4MP	1/3", 4 megapixel, progressive scan, CMOS, Colour: 0.02 Lux (F1.6, AGC ON), 0 Lux with IR, True WDR 120db, Max Res. 2592x1520, H.265, H.264, MJPEG, 4MP (2560x1440): Max. 25 fps, Micro SD, up to 128GB, IK10, IP66.	VT 36,600
IPC868ER-VF18		4K	1/1.7" CMOS, ICR, 12MP (4000x3000): 20fps; 4K (3008x3000): 25fps, H.264, 6 stream: fisheye, panoramic, 4 ePTZ, DC 12V & PoE, 120dB WDR, Micro SD card slot, Alarm in/out 2/1, Audio & Mic & Speaker, BNC output, IP66 & IK10, 1.8mm fixed lens, IR range: 20m	VT 99,000

Model	Product image	Camera inputs	Description	Vatu (Ex-Vat)	
Bullet cameras					
IPC2122SR3-PF40B		2MP	1/2.7" CMOS, ICR, 1920x1080:30fps, H.265/H.264/MJPEG, Triple streams, DC12V & PoE, IP66, Fixed lens(4.0mm, 6.0mm optional), IR range: up to 30m, IR anti-reflection window, Built-in bracket	VT	14,400
IPC2122SR3-UPF40 STARLIGHT		2MP	1/2.9", 2MP CMOS, 4.0mm lens Angle of view(H): 76.6°H.265/H.264/MJPEG, Triple streams, DC12V & PoE, IP66, Fixed lens(4.0mm, 6.0mm optional), IR range: up to 30m, IR anti-reflection window, Built-in bracket	VT	16,800
IPC2222SR5-DPF40B STARLIGHT		2MP	1/3" CMOS, ICR, 2592*1520: 20fps; 2560*1440: 25fps, H.265/H.264/MJPEG, Triple streams, DC12V & PoE, 120dB WDR, IP66, IR range: up to 50m. Fixed lens 4.0mm	VT	21,000
IPC2224SR5-DPF40 IPC2224SR5-DPF60		4MP	1/3" CMOS, ICR, 2592*1520: 20fps; 2560*1440: 25fps, H.265/H.264/MJPEG, Triple streams, DC12V & PoE, 120dB WDR, IP66, IR range: up to 50m. (optional 4mm, 6mm lens)	VT	20,400
IPC2125SR3-ADUPF40(60)		5MP	1/2.7", progressive scan, 5.0megapixel, CMOS, Lens 4.0mm@F1.6, Angle of View(H) 86.9°, 54.05°, Colour: 0.005 Lux (F1.6, AGC ON), 0 Lux with IR on, IR Range Up to 30m IR range, Digital Defog, WDR	VT	16,800
IPC2322EBRP		2MP	1/2.8" CMOS, ICR, 1920x1080:30fps, H.264/MJPEG, Triple streams, AC 24V & DC12V & PoE, 3D DNR, Corridor mode, ROI, Micro SD card slot, Alarm in/out 2/1, Audio, BNC output, IP66, Manual 2.8-12mm Varifocal lens, IR range: up to 30m, NAA(Network-auto-adaptability), Defog, IR anti-reflection window	VT	27,600
IPC2325EBR5-DUPZ		5MP	1/2.7", progressive scan, 5.0megapixel, CMOS, Lens 2.7~13.5mm, AF automatic focusing and motorized zoom lens, Angle of View(H) 93.38°~28.56°(H), Minimum Illumination: Colour: 0.001 Lux (F1.2, AGC ON) 0 Lux with IR on, IR Range Up to 50m, Digital Defog, WDR	VT	31,800
IPC2328SBR5-DPZ		4K	1/2", progressive scan, 8.0megapixel, CMOS, 2.8~12mm, AF automatic focusing and motorized zoom lens, Colour: 0.003 Lux (F1.5, AGC ON), 0 Lux with IR on, IR-cut filter with auto switch (ICR), Digital noise reduction 2D/3D DNR, S/N >52dB, IR Range Up to 50m, Digital Defog, WDR 120 dB	VT	51,000
IPC742SR9-PZ30-32G		2MP	1/2.8" CMOS, ICR, 2MP, H.265/H.264/MJPEG, Triple streams, DC12V & PoE, IP66, 3-6mm 2X Motorised optical zoom, IR range: up to 100m, IR anti-reflection window, Built in 32G EMMC storage. Motorised Pan: 250°, Tilt: -50°--50°. 400 presets.	VT	40,800
IPC744SR5PF4032G		4MP	1/3" CMOS, ICR, 2592*1520: 20fps; 2560*1440: 25fps, H.265/H.264/MJPEG, Triple streams, DC12V & PoE, IP66, Fixed 4mm lens, IR range: up to 50m, Built-in. 32G EMMC storage. Pan: 250°, Tilt: -50°--50°. 400 presets.	VT	45,000
IPC744SR5PF6032G		4MP	1/3" CMOS, ICR, 2592*1520: 20fps; 2560*1440: 25fps, H.265/H.264/MJPEG, Triple streams, DC12V & PoE, IP66, Fixed 6mm lens, IR range: up to 50m, Built-in. 32G EMMC storage. Pan: 250°, Tilt: -50°--50°. 400 presets.	VT	48,600
IPC262ER9-DUZ		2MP	1/2.8" CMOS, ICR, 1920x1080:30fps, H.265/H.264/MJPEG, Triple stream, AC 24V & DC12V & PoE, 120dB WDR, Micro SD card slot, Alarm in/out 2/1, Audio, BNC output, IP67, 2.8-12mm Motorized Varifocal lens, 4X optical zoom with Auto Focus, IR anti-reflection window, Bulit-in bracket. IR range: up to 100m. Starlight: 0.002 Lux min. illumination	VT	72,000
IPC262ER9X10DU		2MP	1/2.8" CMOS, IP67, 2.8-12mm, motorised 4X optical zoom .265/H.264/MJPEG, AC 24V & DC12V & PoE, 120dB WDR, Micro SD card slot, Alarm in/out 2/1, Audio, BNC output, , IR range: up to 100m. Ultra low-light(Starlight)120dB WDR, IP67, 100m IR, Starlight	VT	84,000
IPC252ERA-X22DUG		2MP	1/1.9" CMOS, ICR, 1920x1080:30fps, H.265/H.264/MJPEG, Triple stream, AC 24V, 120dB WDR, Micro SD card slot, Alarm in/out 2/1, Audio, BNC output, IP67, 6.5-143mm, 22X optical zoom, IR range: up to 200m. Ultra low-light Starlight	VT	127,800
IPC268ER9-DZ		4K	1/2.5" 8MP, progressive scan CMOS, 3840x2160 resolution, 30fps, Smart IR, up to 100m IR distance, H.265, ONVIF, DC12V, AC24V, PoE. Wide voltage range of ±25%, IP67	VT	119,400

Model	Product image	Camera inputs	Description	Vatu (Ex-Vat)
IPC542E-DLC		2MP	1/2.8" CMOS, ICR, 1920x1080:30fps, 1280x720:30fps, H.264/MJPEG, Triple streams, AC 24V & DC12V & PoE, 120dB WDR, SD card slot, Alarm in/out 2/1, Audio, BNC output, Zoom/Focus interface	VT 37,800
IPC562E-DUG		2MP	1/1.9" progressive scan CMOS, Up to 1920 x 1080 resolution, 60fps, 120dB True WDR, ABF, Optical fiber interface, HLC, 3D DNR, ROI, Corridor Mode, ONVIF, Motor Zoom/focus ports, AC24V, DC12V, PoE. Wide voltage range of ±25% WITH SFP Fibre Port	VT 71,400
IPC568E-G		4K	1/1.7" CMOS, ICR, 8MP (4000x3000):20fps, 4K (3840x2160):30fps, H.265/H.264/MJPEG, Triple streams, AC 24V & DC12V & PoE, SD card slot, Alarm in/out 2/1, Audio, BNC output, Zoom/Focus interface, SFP Slot+RJ45, Optical Defog & Digital Defog, WITH SFP Fibre Port	VT 111,600
PTZ				
IPC6322SR-X22P-C		2MP	1/2.9" progressive scan, 2.0megapixel, CMOS, Lens 5.2~ 114.4 mm (22x optical zoom), AF automatic focusing and motorized zoom lens, Angle of View (H) 54.40° (wide) ~ 3.44° (tele), IR Range upto 150m, Digital Defog, DWDR	VT 60,000
IPC6222ER-X20(P)B		2MP	1/3", progressive scan, 2.0megapixel, CMOS, Lens 5.2 ~ 104 mm (20x optical zoom), AF automatic focusing and motorized zoom lens, Angle of View (H) 60.19° (wide) ~ 3.0° (tele) Minimum Illumination Colour: 0.01 lux (F1.5, AGC ON), 0 lux with IR, IR Range UP to 150m, Digital Defog, DWDR	VT 95,880
IPC6222ER-X30(P)B		2MP	1/2.8", progressive scan, 2.0megapixel, CMOS, Lens 4.5 ~ 135 mm (30x optical zoom), AF automatic focusing and motorized zoom lens, Angle of View (H) 62.67° (wide) ~ 2.82° (tele) Minimum Illumination- Colour: 0.01 lux (F1.6, AGC ON), 0 lux with IR, IR Range Up to 150 m, Digital Defog, DWDR	VT 119,760
IPC6222E-X33UP		2MP	1/2.8", progressive scan, 2.0megapixel, CMOS, 4.5~ 148.5mm, AF automatic focusing and motorized zoom lens, Digital Zoom x 16, Optical Zoom x 33, Angle of View (H) 62.67°~2.82°, Angle of View (V) 38.4°~1.3°, Angle of View (O) 77.1°~3.3°, IR-cut filter with auto switch (ICR), Digital Defog, True WDR 120dB.	VT 115,800
IPC642E-X22I-IN		2MP	1/2.8" CMOS, ICR, 1920x1080:25fps, H.264/MJPEG, Triple streams, PoE+, 24VAC, 3D DNR, SD card slot, Alarm in/out 2/1, Audio, BNC output, -40~70°C, IP66, 22x optical zoom (4.7 ~ 103mm)	
IPC6252SR-X33U		2MP	1/2.8" CMOS, ICR, 1920x1080:60fps, H.265/H.264/MJPEG, Triple streams, AC24V/DC24V, Micro SD card slot, Alarm in/out 2/1, Audio, BNC output, -40~70°C, IP66, 33x optical zoom (4.5 ~ 148.5mm), IR range: up to 200m, IR anti-reflection window, Ultra low-light (Starlight)	VT 156,000
IPC6252SL-X33UP		2MP	UNV 2MP 33X Starlight Laser IR Network PTZ Dome Camera (5", RJ45, PoE, H.265)	VT 256,200
IPC6258SR-X22		4K	1/1.7", progressive scan, 12.0megapixel, CMOS, 6.5~ 143 mm (22x optical zoom), AF automatic focusing and motorized zoom lens, IR Range upto 200m, Digital Defog, DWDR	VT 276,000
IPC6858SR-X22		4K	1/1.7" CMOS, ICR, 12MP (4000x3000):20fps, 4K (3840x2160):30fps, H.264/H.265/MJPEG, Triple streams, AC24V/DC24V, SD card slot, Alarm in/out 2/1, Audio, BNC output, -45~70°C, IP66, 22x optical zoom (6.5 ~ 143mm), IR range: up to 250m	VT 352,200
IPC6852SR-X44U		2MP	1/2.8" CMOS, ICR, 1920x1080:60fps, H.265/H.264/MJPEG, Triple streams, AC24V/DC24V, SD card slot, Alarm in/out 2/1, Audio, BNC output, -45~70°C, IP66, 44x optical zoom (5 ~ 220mm), IR range: up to 250m, Ultra low-light (Starlight), Optical Defog & Digital Defog,	VT 360,000
PWR-DC5611			POE Injector 60W	VT 19,800

Model	Product image	Camera inputs	Description	Vatu (Ex-Vat)
Lens & Brackets				
DM3816D			3.8mm-16mm, 3MP CS Mount, F1.6, DC auto-Iris, suitable for starlight sensor cameras	VT 17,400
DM1250D			12-50mm, 3MP CS Mount, F1.6, DC auto-Iris, suitable for starlight sensor cameras	VT 30,840
TR-WE45			Wall Bracket suits PTZ's direct, and mini domes by using AE-TR-UF45-D-IN	VT 2,400
AE-TR-UF45-D-IN			Adapter plate suits IPC32x & IPC36xx series mini domes	VT 1,800
TR-UF45-BIN			UNV Ceiling Mount Plate for pendant	VT 1,800
TR-CE45-IN			Indoor or outdoor, PTZ Dome Pendant installation 116.5mmx239mm Aluminium alloy	VT 2,400
TR-SE45				VT 2,400
TR-UM06-BIN				VT 960
TR-UP06-A-IN			Pole mount ECO	VT 1,200
TR-UP06-IN			Pole mount	VT 1,800
TR-UP08-A			Pole mount for AE-TR-WE45 wall bracket	VT 3,600
TR-UC08-A-IN			Corner mount	VT 3,600
TR-JB05-IN			Suits mini bullets	VT 2,400
AE-TR-JB07			Cable junction box. IPC2XX and IPC32X series. Also suits Wall Brackets TR-WM03IN/TR-WM04IN. 126mmx125mmx55mm Aluminium alloy	VT 3,600
TR-JB12-IN			Outdoor or indoor cable junction box for PTZ Dome series, 296mmx244mmx127mm (11.7" x9.6" x5")	VT 10,800
TR-JB03-A-IN			Aluminium Alloy, 126mmx36mm. Suits IPC322 Mini Vandal Dome Series	VT 1,800
TR-JB03-B-IN			Aluminium Alloy, 126mmx36mm. Suits IPC312/314 Mini Vandal Dome Series	VT 1,800

Model	Product image	Camera inputs	Description	Vatu (Ex-Vat)	
TR-JB03-C-IN			Aluminium Alloy, 126mmx36mm. Suits IPC3612 Mini Vandal Dome Series suit metal base version	VT	1,800
TR-JB03-E-IN			Aluminium Alloy, 126mmx36mm. Suits Metal Turrets	VT	1,800
TR-WM03IN			Aluminium Alloy. 188mmx126mmx126mm. Suits IPC3612/322 Series	VT	1,800
TR-JB04IN			Aluminium Alloy, 208mmx125mmx125mm. Suits IPC3232 Varifocal Series	VT	1,800
TR-WM04IN			Aluminium Alloy. 208mmx125mmx125mm. Suits IPC3232 Varifocal Series.	VT	1,800
TR-FM200IN			Indoor PTZ Dome In Ceiling Mount. Suits IPC 6 Series PTZ Domes	VT	6,600
TR-FM152AIN			In Ceiling Mount. Suits IPC3232 Domes	VT	4,200
TR-UM06-IN			Pendant or wall installation for box camera	VT	4,200
HS-215SHB-IN			Outdoor Housing for box camera (including sun shade, heater and fan) -40°C ~60°C Humidity ≤ 90% RH(non-condensing) Inside: 280x100x80mm. Requires Bracket	VT	21,000
TR-WM06-B-IN			Outdoor, wall bracket for box camera housing	VT	3,000
TR-UV06-A-IN			Adjustable bracket /platform	VT	2,400